

PIPE CLIPS ZE



Pipe clips ZE have the full functionality of metal fasteners plus a number of new advantages:

- Tensile strength is not less or exceeds this parameter of most metal pipe clips (as their soft spot is the nut welded to bracket). Typical pipe holding force - minimum 300 kg (661.39 lb). Version with additional lugs - 500 kg (1102.31 lb). This fastener design has no hidden defects/soft spots, pipes are secured with standard metalware (studs, nuts, collets).
- Ability to bundle pipes in several layers, tightly or sparsely (M6, M8, M10, M12);



As a result, you will have a securely laid system with free sliding fastening and stable slope which you set once and automatically observe throughout the pipe bundle. This system is easy to maintain: Fast and easy replacement of single pipes and adding more pipes to the line.

- Full pipe vibration absorption;
- Free sliding fastening (to prevent pipe distortion caused by thermal expansion in segments between expansion bends (loops, elbows);
- Ability to automatically set a clear guaranteed slope of several pipes line by predefined angle for one pilot pipe (see mounting example photo);
- Quick mounting and adjustment;

- Simple installation of additional pipes;



- Simple maintenance and repair of pipe lines, simple pipe replacement;
- No corrosion;
- Ability to paint fasteners in any colour;
- Thermally insulated (heat insulated) fasteners.